



CONTAMINATION CONTROL

Airborne Particle Counters



Features and Benefits

- Multiplexed monitoring for up to 32 locations
- Short purge time
- Economical price per point sampling
- Bi-directional control capability
- Sample runs of up to 38.1 m
- Programmable sampling point sequences
- Controlled by FMS 5 Software
- Compatible with 28.3 L/min (1 CFM) AEROTRAK™ Portable Particle Counters
- Integrated controller minimizes complexity
- Port for pressure sensor to ensure vacuum flow

Aerosol Sampling Manifold
Model M32-01

The TSI Model M32-01 Manifold offers an affordable solution for monitoring multiple locations in large areas with a single particle counter. The Model M32-01 can provide important trend analysis and clean room verification. The product has 32 sampling ports and is compatible with TSI 28.3 L/min (1 CFM) AEROTRAK™ Portable Particle Counters, including those down to 0.1 μm sensitivity. The Manifold is controlled via FMS 5 Software, allowing the user to configure and control the system to meet their requirements.

The Model M32-01 is backed by TSI's long-standing reputation as the recognized standard for particle measurements and with a two-year warranty.



TRUST. SCIENCE. INNOVATION.

CONTAMINATION CONTROL

Airborne Particle Counters

Specifications Model M32-01 Aerosol Sampling Manifold

Features	Manifold System
Sample Ports	32-port capability
Compatibility	Operates with 28.3 L/min (1 CFM) TSI AeroTRAK™ Portable Particle Counters

Features	Manifold Blower Requirements
Blowers Required	One
Flow Rate*	>170 m³/hr

*Based on using all 32 sampling ports. Lower flow rates are acceptable when <32 sampling ports are used.

Features	Manifold Module
Flow Rate	Nominal 85.0 L/min (3 CFM)
Purge Time	<10 seconds
Cross Talk	<0.2% cross talk between ports
Sample Tubing Size	3/8" ID, 1/2" OD
Sample Tubing Length	38.1 m capability per port, avoiding bends or kinks in tubing
Fitting Provided	Barbed fitting to accept 3/8" ID tubing
Control	Manifold is controlled by FMS 5 software or by HyperTerminal to send commands to Manifold
Communication Protocol	RS-232
Software Compatibility	FMS 5 software
Directional Control	Bi-directional stepper motor
Mounting	Holes in mounting feet
Power	24 VDC, 4.0 A
Dimensions (HWD)	27.2 cm x 27.2 cm x 32.8 cm
Weight	4.54 kg
Operating Conditions	15° to 45°C; up to 85% RH noncondensing
Warranty	Two years
Reference Position	Integrated home sensor
Included Accessories	Operating manual on CD, connectors for power, and communications
Optional Accessories	Isokinetic sampling probes, sample tubing, blower

Specifications are subject to change without notice. TSI, the TSI logo, AEROTRAK, and TRAKPRO are trademarks of TSI Incorporated.

TSI Incorporated - 500 Cardigan Road, Shoreview, MN 55126-3996 USA
USA Tel: +1 800 874 2811 E-mail: info@tsi.com Website: www.tsi.com
UK Tel: +44 149 4 459200 E-mail: tsiuk@tsi.com Website: www.tsiinc.co.uk
France Tel: +33 491 11 87 64 E-mail: tsifrance@tsi.com Website: www.tsiinc.fr
Germany Tel: +49 241 523030 E-mail: tsigmbh@tsi.com Website: www.tsiinc.de
India Tel: +91 80 41132470 E-mail: tsi-india@tsi.com
China Tel: +86 10 8251 6588 E-mail: tsibeijing@tsi.com
Singapore Tel: +65 6595 6388 E-mail: tsi-singapore@tsi.com



TRUST. SCIENCE. INNOVATION.

Contact your local TSI Distributor or visit our website www.tsi.com for more detailed specifications.